## NSN 5905-00-010-0636

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-010-0636 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.0620 inches Pilot Length: 0.0930 inches **Undercut Diameter:** 1.562 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 1.750 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Body Length:** 2.000 inches **Mounting Lip Diameter:** 1.5620 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 356.0 **Maximum Starting Torque:** 1.75 inch-ounces

**Maximum Stop Torque:** 

1.75 inch-ounces

**Nonturn Device Location:** 

At 3 oclock

**Nonturn Device Radius:** 

1.062 inches

## NSN 5905-00-010-0636

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.001 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.00200 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Electrical Resistance Per Section:
5.0 percent, rated amperes c and better finish and 10.0 percent, rated amperes c and better industrial clears
Rotary Actuator Travel In Angular Deg:
356.0
Function Conformity Tolerance Per Section:
-0.15/+0.15 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 all sections
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary at 10'30 oclock
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
6 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Terminal Type And Quantity:
6 turret
Shelf Life:
N/a
Unit Of Measure:

-

## NSN 5905-00-010-0636

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0