## NSN 5905-00-010-5383

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-010-5383 **Section Quantity:** 1 **Body Style:** Rectangular w/bushing **Reliability Indicator:** Not established **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.562 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** 1.062 inches

**Body Width:** 0.750 inches **Body Height:** 0.484 inches

**Shaft Style:** Round, slotted **Actuator Type:** 

Single shaft

**Nonturn Device Location:** 

At 9 oclock

**Nonturn Device Radius:** 

0.234 inches

**Screw Thread Diameter:** 

0.250 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Locking bushing

**Features Provided:** 

Nonmetallic shaft and panel seal

**Electrical Resistance Per Section:** 

500.0 ohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

## NSN 5905-00-010-5383

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watt	s:
--	----

1.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A002a0