## NSN 5905-00-011-7112

**Section Quantity:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-011-7112

Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.500 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.687 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.453 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
Nonturn Device Radius: 0.245 inches
0.245 inches
0.245 inches  Screw Thread Diameter:
0.245 inches  Screw Thread Diameter:  0.375 inches
0.245 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:
0.245 inches  Screw Thread Diameter: 0.375 inches  Screw Thread Series Designator: Unef
0.245 inches  Screw Thread Diameter: 0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi):
0.245 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0
0.245 inches  Screw Thread Diameter: 0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location:
0.245 inches  Screw Thread Diameter: 0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Rear end
0.245 inches  Screw Thread Diameter: 0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Rear end  Mounting Method:
0.245 inches  Screw Thread Diameter: 0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Rear end  Mounting Method: Standard bushing
0.245 inches  Screw Thread Diameter: 0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Rear end  Mounting Method: Standard bushing  Electrical Resistance Per Section:
0.245 inches  Screw Thread Diameter: 0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Rear end  Mounting Method: Standard bushing  Electrical Resistance Per Section: 3.0 kilohms single section
0.245 inches  Screw Thread Diameter: 0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Rear end  Mounting Method: Standard bushing  Electrical Resistance Per Section: 3.0 kilohms single section  Power Dissipation Rating Per Section In Watts:
0.245 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Rear end  Mounting Method: Standard bushing  Electrical Resistance Per Section: 3.0 kilohms single section  Power Dissipation Rating Per Section In Watts: 2.0 free air single section
0.245 inches  Screw Thread Diameter: 0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Rear end  Mounting Method: Standard bushing  Electrical Resistance Per Section: 3.0 kilohms single section  Power Dissipation Rating Per Section In Watts: 2.0 free air single section  Resistance Tolerance Per Section In Percent:

## NSN 5905-00-011-7112

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0