

View Online at https://aerobasegroup.com/nsn/5905-00-012-2003

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-10.0 to 10.0

#### **Electrical Resistance:**

143.000 kilohms

**Resistance Tolerance In Percent:** 

-0.100 to 0.100

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

145.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-65.0 to 145.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Type:**

# Wire lead

Reliability Indicator:

#### Established

**Reliability Failure Rate Level In Percent:** 

0.010

## **Terminal Length:**

1.500 inches

#### Body Diameter:

0.375 inches

# Body Length:

0.750 inches

## **Power Dissipation Rating In Watts:**

0.333 free air

## **Unpackaged Unit Weight:**

5.000 grams

## Style Designator:

Axial terminal each end

## Test Data Document:

81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-39005/2 government specification

# Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

# NSN 5905-00-012-2003

Noninductive Wire Wound Fixed Resistor - Page 2 of 2

Fiig: A001a0

