## NSN 5905-00-012-2520

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-012-2520

Electrical Resistance: 17.500 ohms Resistance Tolerance in Percent: 17.500 ohms Resistance Tolerance in Percent: 125.0 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 to 145.0 Inclosure Method: Incapsulated Reliability Indicator: 125.0 inches 125.0 inc	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 Inclosure Method: Incapsulated Ferminal Type: Wire lead Retiability Indicator: Note established 30dy Diameter: 0.250 inches 30dy Length: 0.750 inches 70ver Dissipation Rating In Watts: 0.250 free air 8tyle Designator: Xxial terminal each end Feet Data Document: 914349-mill-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Dirit Of Measure: - Demilitarization: No	-20.0 to 20.0
Resistance Tolerance In Percent: 1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 Tempurature Method: Temposulated Terminal Type: Wire lead Reliability Indicator: Rote established 30ady Diameter: 10.250 inches 30ady Length: 10.750 inches 30ady Length: 10.750 inches 30ady Ength: 10.750	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 Inclosure Method: Incapsulated Terminal Type: Wive lead Reliability Indicator: Not established 30dy Diameter: 1.250 inches 30dy Length: 1.750 inches Power Dissipation Rating In Watts: 1.250 free air Style Designator: 1.3434-mil93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Juitt Of Measure: - Demilitarization: No	47.500 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Fernpurature Range Of Tempurature Coefficient In Deg Celsius:  85.0 to 145.0  Inclosure Method:  Encapsulated  Ferninal Type:  Wire lead  Reliability Indicator:  Not established  30xdy Diameter:  1.250 inches  30xdy Diameter:  1.250 inches  30xdy Length:  1.750 inches  30xdy Ength:  30xdy En	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Crempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0 to 145.0  Inclosure Method:  Incapsulated  Cerminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  10.250 inches  Body Length:  10.750 inches  Power Dissipation Rating In Watts:  10.250 free air  Style Designator:  Availateminal each end  Fest Data Document:  81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Via  Unit Of Measure:  - Demilitarization:  No	-1.000 to 1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Fempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0  Inclosure Method: Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator: Not established  Body Diameter: 10.250 inches  Body Length: 10.750 inches  Power Dissipation Rating In Watts: 10.250 free air  Style Designator: Axial terminal each end  Fest Data Document: 11349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Juit Of Measure: - Demilitarization: No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Rempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 nclosure Method: Encapsulated Reminal Type: Write lead Reliability Indicator: Not established Rody Diameter: 0.250 inches Rody Diameter: 0.250 inches Rody Dissipation Rating In Watts: 0.250 free air Rytyle Designator: Axial terminal each end Rest Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: V/a Juit Of Measure: - Demilitarization: No	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0 to 145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Note established  Body Diameter:  10.250 inches  Body Length:  10.750 inches  Power Dissipation Rating In Watts:  10.250 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mill-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Diameter: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Avail terminal each end Fest Data Document: 81349-mill-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Wa Juit Of Measure: Demilitarization: No	145.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Avial terminal each end Fest Data Document: B1349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:  Wa Unit Of Measure: - Demilitarization: No	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Juit Of Measure: - Demilitarization: No	-65.0 to 145.0
Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.250 inches  Body Length:  0.750 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end  Fest Data Document:  81349-mill-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Jinit Of Measure:  Demilitarization:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Encapsulated
Reliability Indicator: Not established  Body Diameter: 0.250 inches  Body Length: 0.750 inches  Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Axial terminal each end  Fest Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure: - Demilitarization: No	Terminal Type:
Note established  Body Diameter:  D.250 inches  Body Length: D.750 inches  Power Dissipation Rating In Watts: D.250 free air  Style Designator: Axial terminal each end  Fest Data Document: B1349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  W/a  Juit Of Measure:  Demilitarization:	Wire lead
Body Length: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Reliability Indicator:
2.250 inches 3.360dy Length: 2.750 inches 2.	Not established
Body Length:  0.750 inches  Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Axial terminal each end  Fest Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure: - Demilitarization: No	Body Diameter:
Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end  Test Data Document:  31349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	0.250 inches
Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization:	Body Length:
O.250 free air Style Designator: Axial terminal each end Fest Data Document: B1349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	0.750 inches
Axial terminal each end  Fest Data Document:  31349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end  Fest Data Document:  81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	0.250 free air
Fest Data Document:  81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  8helf Life:  N/a  Unit Of Measure:  Cemilitarization:	Style Designator:
B1349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  - Demilitarization:	81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life: N/a  Jnit Of Measure: - Demilitarization:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a  Jnit Of Measure:  - Demilitarization:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: - Demilitarization:	Shelf Life:
- Demilitarization:	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Filig:	No
	Fiig:
\001a0	A001a0