NSN 5905-00-013-9062

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-013-9062

Electrical Resistance: 300.000 ohms Resistance Tolerance In Percent: -0.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 300.000 ohms Resistance Tolerance In Percent: -1.010 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/4275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: -0.125 inches Body Length: 2.000 free air Style Designator: Axial terminal each end Test Data Document 28640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Date: 30840-6083726 manufacturers source control Sheft Life: Na Unit Of Measure:	
SRESIEROR FORFANCE IN PERCENT -0.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: -0.125 inches Body Length: -0.515 inches Power Dissipation Rating In Watts: -2000 free air Style Designator: Avail terminal each end Test Data Document: -0.84840-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: -0.8406-06083726 manufacturers source control Shelf Life: Na Unit Of Measure:	
Resistance Tolerance In Percent: -0.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+275.0 Iteliciosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.125 inches Power Dissipation Rating In Watts: 2,000 free air Style Designator: Axial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Sheft Life: Na Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+275.0 Inclosure Method: Encapsulated Terrinal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.515 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Avial terminal each end Test Data Document: 0.3640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: Unit Of Measure:	
25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.515 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification Data: 03640-6083726 manufacturers source control Shelf Life: Na Unit Of Measure: - Demilitarization: No Fig:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+275.0 Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.515 inches Power Dissipation Rating In Watts: 2,000 free air Style Designator: Axial terminal each end Test Data Document: 03640-60083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification Data: 03640-60083726 manufacturers source control Shelf Life: Na Unit Of Measure: - Demilitarization: No Fig:	
Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.04-275.0 inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.516 inches Power Dissipation Rating in Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-65.0/4275.0 inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.515 inches Power Dissipation Rating in Watts: 2.000 free air Style Designator: Avial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Sheft Life: N/a Unit Of Measure: Demilitarization: No Fig:	
-65.0/4275.0 inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.515 inches Power Dissipation Rating in Watts: 2.000 free air Style Designator: Avial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Sheft Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.515 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	-65.0/+275.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.515 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.515 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.515 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Not established Body Diameter: 0.125 inches Body Length: 0.515 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Diameter: 0.125 inches Body Length: 0.515 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
0.125 inches Body Length: 0.515 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Length: 0.515 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 0.3640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 0.3640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
0.515 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.125 inches
Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
2.000 free air Style Designator: Axial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.515 inches
Style Designator: Axial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	2.000 free air
Test Data Document: 03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Specification Data: 03640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Specification Data: 03640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	03640-6083726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
O3640-6083726 manufacturers source control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	03640-6083726 manufacturers source control
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0