Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-013-9568

Section Quantity:	
1	
Body Style:	
Rectangular w/mounting holes	
Reliability Indicator:	
Not established	
Terminal Length:	
Between 0.285 inches and 0.315 inches	
Mounting Hole Diameter:	
0.074 inches	
Shaft Diameter:	
Between 0.080 inches and 0.100 inches	
Shaft Length:	
Between 0.030 inches and 0.050 inches	
Body Length:	
Between 0.360 inches and 0.390 inches	
Body Width:	
Between 0.187 inches and 0.219 inches	
Body Height:	
Between 0.360 inches and 0.390 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Effective Electrical Rotation In Deg Angular	Rotation:
9000.0	
Center To Center Distance Between Termin	als:
Between 0.190 inches and 0.210 inches	
Lateral Distance Between Mounting Hole Ce	nters:
0.419 inches	
Mounting Facility Quantity:	
1	
Terminal Location:	
Upper adjacent side single row	
Mounting Method:	
Unthreaded hole and terminal	
Electrical Resistance Per Section:	
10.0 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
9000.0	
Center To Center Distance Between Center	Terminal And Outside Terminal:



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0 to 100.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0