NSN 5905-00-013-9679

Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-013-9679

-20.07+20.0 Electrical Resistance: 1.0000 chms Resistance Tolerance in Percent: -1.0007+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -56.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Langth: 0.220 inches Power Dissipation Rating in Watts: 0.230 free air Sylve Designator: Axial terminal each end Tost Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit of Measure: - Demilitarization: No Filig: A00130	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: -Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: -1.0180 inches Rody Length: -2.200 inches Power Dissipation Rating In Watts: -0.303 free air Style Designator:	-20.0/+20.0
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-96000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	Electrical Resistance:
1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diamete: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	10.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Dameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.303 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Filgs:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.303 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Lingth: 0.108 inches Body Longth: 0.220 inches Power Dissipation Rating In Watts: 0.303 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: Na Unit Of Measure: - Demilitarization: No Fig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating in Watts: 0.303 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.303 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure: Demilitarization: No Filg:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating in Watts: 0.303 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure: Demilitarization: No Fig:	145.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating in Watts: 0.303 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure: Demilitarization: No Filig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0,108 inches Body Length: 0,220 inches Power Dissipation Rating In Watts: 0,303 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Filg:	-55.0 to 125.0
Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Encapsulated
Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.303 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Noinductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Wire lead
Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reactance Characteristic:
Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Noninductive
Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Not established
Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.108 inches
Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
O.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.220 inches
Style Designator: Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.030 free air
Test Data Document: 14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	14804-b6000013606 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment
N/a Unit Of Measure: Demilitarization: No Fiig:	manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	-
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0