NSN 5905-00-013-9680

Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-013-9680

| Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, |
|--|
| Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing |
| Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Length: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.303 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing; |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, |
| -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, |
| Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, and the contractor drawing. |
| Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| Noninductive Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| Reliability Indicator: Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| Not established Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing; Shelf Life: |
| 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| Style Designator: Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| Axial terminal each end Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| Test Data Document: 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| 14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. |
| manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing |
| |
| Shelf Life: |
| |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A001a0 |