## NSN 5905-00-013-9682

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-013-9682

Electrical Resistance: 13.000 ohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.875 inches Body Diameter: -0.108 inches Body Length: -0.220 inches Power Dissipation Rating In Watts: -0.030 free air Style Designator:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
13.000 ohms  Resistance Tolerance in Percent: -1.000 to 1.000  Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 125.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead Reliability Indicator: Not established  Terminal Length: -1.875 inches  Body Diameter: -0.108 inches  Body Diameter: -0.220 inches  Power Dissipation Rating in Watts: -0.230 free air  Style Designator: Axial terminal each end  Test Data Document: -14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing;  N/a  Unit Of Measure:	-20.0/+20.0
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.875 inches Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing; N/a Unit Of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Terminal Length: 1.875 inches Body Diameter: 0.108 inches Body Diameter: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing; Sheff Life: N/a Unit Of Measure:	13.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.875 inches Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing; Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0 to 125.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.875 inches  Body Diameter:  0.108 inches  Body Length:  0.220 inches  Power Dissipation Rating In Watts:  0.300 free air  Style Designator:  Axial terminal each end  Test Data Document:  14804-5600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing; Sheff Life:  N/a  Unit Of Measure:	-1.000 to 1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length: -1.875 inches  Body Diameter: -0.108 inches  Body Diameter: -0.220 inches  Power Dissipation Rating In Watts: -0.303 free air  Style Designator:  Axial terminal each end  Test Data Document: -14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.875 inches Body Diameter: 0.108 inches Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.875 inches Body Diameter: 0.108 inches Body Diameter: 0.109 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing! Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.875 inches Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing; Shelf Life: N/a Unit Of Measure:	145.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.875 inches Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.875 inches Body Diameter: 0.108 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.030 free air Style Designator: Axial terminal each end Test Data Document: 14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing; Shelf Life: N/a Unit Of Measure:	-55.0 to 125.0
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.875 inches  Body Diameter:  0.108 inches  Body Length:  0.220 inches  Power Dissipation Rating In Watts:  0.030 free air  Style Designator:  Axial terminal each end  Test Data Document:  14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing;  Shelf Life:  N/a  Unit Of Measure:	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.875 inches  Body Diameter:  0.108 inches  Body Length:  0.220 inches  Power Dissipation Rating In Watts:  0.030 free air  Style Designator:  Axial terminal each end  Test Data Document:  14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Encapsulated
Reliability Indicator:  Not established  Terminal Length:  1.875 inches  Body Diameter:  0.108 inches  Body Length:  0.220 inches  Power Dissipation Rating In Watts:  0.030 free air  Style Designator:  Axial terminal each end  Test Data Document:  14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Terminal Type:
Note established  Terminal Length:  1.875 inches  Body Diameter:  0.108 inches  Body Length:  0.220 inches  Power Dissipation Rating In Watts:  0.030 free air  Style Designator:  Axial terminal each end  Test Data Document:  14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Wire lead
Terminal Length:  1.875 inches  Body Diameter:  0.108 inches  Body Length:  0.220 inches  Power Dissipation Rating In Watts:  0.030 free air  Style Designator:  Axial terminal each end  Test Data Document:  14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Reliability Indicator:
1.875 inches  Body Diameter: 0.108 inches  Body Length: 0.220 inches  Power Dissipation Rating In Watts: 0.030 free air  Style Designator: Axial terminal each end  Test Data Document: 14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing; Shelf Life: N/a  Unit Of Measure:	Not established
Body Diameter:  0.108 inches  Body Length: 0.220 inches  Power Dissipation Rating In Watts: 0.030 free air  Style Designator: Axial terminal each end  Test Data Document: 14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Terminal Length:
0.108 inches  Body Length: 0.220 inches  Power Dissipation Rating In Watts: 0.030 free air  Style Designator:  Axial terminal each end  Test Data Document: 14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	1.875 inches
Body Length:  0.220 inches  Power Dissipation Rating In Watts:  0.030 free air  Style Designator:  Axial terminal each end  Test Data Document:  14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Body Diameter:
0.220 inches  Power Dissipation Rating In Watts: 0.030 free air  Style Designator:  Axial terminal each end  Test Data Document: 14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	0.108 inches
Power Dissipation Rating In Watts:  0.030 free air  Style Designator:  Axial terminal each end  Test Data Document:  14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Body Length:
0.030 free air  Style Designator:  Axial terminal each end  Test Data Document:  14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	0.220 inches
Style Designator:  Axial terminal each end  Test Data Document:  14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	0.030 free air
Test Data Document:  14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing).  Shelf Life:  N/a  Unit Of Measure:	Style Designator:
14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Axial terminal each end
manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Test Data Document:
Shelf Life: N/a Unit Of Measure:	14804-b600001304 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment
N/a Unit Of Measure: 	manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing
Unit Of Measure:	Shelf Life:
<del></del>	N/a
 Demilitarization:	Unit Of Measure:
Demilitarization:	
	Demilitarization:
No	No
Fiig:	Fiig:
A001a0	A001a0