## NSN 5905-00-013-9683

Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-013-9683

Electrical Resistance:  14.000 ohms  Resistance Tolerance In Percent:  -1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0 to 125.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reactance Characteristic:  Noninductive  Reliability Indicator:
14.000 ohms  Resistance Tolerance In Percent: -1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reactance Characteristic: Noninductive
Resistance Tolerance In Percent: -1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive
-1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reactance Characteristic: Noninductive
Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0 to 125.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reactance Characteristic:  Noninductive
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reactance Characteristic: Noninductive
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reactance Characteristic: Noninductive
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive
-55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive
Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive
Encapsulated  Terminal Type:  Wire lead  Reactance Characteristic:  Noninductive
Terminal Type: Wire lead Reactance Characteristic: Noninductive
Wire lead  Reactance Characteristic:  Noninductive
Reactance Characteristic: Noninductive
Noninductive
Reliability Indicator:
Not established
Body Diameter:
0.108 inches
Body Length:
0.220 inches
Power Dissipation Rating In Watts:
0.030 free air
Style Designator:
Axial terminal each end
Test Data Document:
14804-b600001306 through b600001350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment
manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0