NSN 5905-00-014-6251

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-014-6251

-500.0/+500.0 Electrical Resistance: 1.3.000 ohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 74.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -40.0 to 74.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Resibality Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit of Measure: Demilitarization: No Filig: A001a0	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
13.000 ohms Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 74.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -4.00 to 74.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; Note Unit Of Measure: Demilitarization: No Elig:	-500.0/+500.0
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 74.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -40.0 to 74.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.400 in Pose piration Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Avial terminal each end Test Data Document: 88932-68972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure:	Electrical Resistance:
-1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 74.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -40.0 to 74.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Tost Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	13.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 74.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -40.0 to 74.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Tost Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 74.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 40.0 to 74.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-1.000 to 1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 74.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -40.0 to 74.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient in Deg Celsius: 40.0 to 74.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.400 inches Power Dissipation Rating in Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -40.0 to 74.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-40.0 to 74.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	74.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-40.0 to 74.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.135 inches Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note established Body Diameter: 0.135 inches Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Diameter: 0.135 inches Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
0.135 inches Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Length: 0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
0.400 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.135 inches
Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
O.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.400 inches
Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Test Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 free air
Style Designator: Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Criticality Code Justification:
Axial terminal each end Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test
Test Data Document: 88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	88932-63972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0