Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-00-015-7249

## Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.300 inches **Terminal Length:** Between 0.469 inches and 0.531 inches **Overall Height:** 0.844 inches **Overall Width:** Between 0.285 inches and 0.295 inches **Mounting Hole Diameter:** Between 0.088 inches and 0.098 inches Shaft Diameter: Between 0.120 inches and 0.130 inches Shaft Length: Between 0.045 inches and 0.055 inches **Body Length:** Between 1.234 inches and 1.266 inches **Body Width:** Between 0.285 inches and 0.295 inches **Body Height:** 0.312 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 Maximum Starting Torque: 8.00 inch-ounces **Center To Center Distance Between Terminals:**

Between 0.695 inches and 0.705 inches

## Lateral Distance Between Mounting Hole Centers:

Between 0.995 inches and 1.005 inches

## **Mounting Facility Quantity:**

2

**Terminal Location:** 

Lower adjacent side two rows

## NSN 5905-00-015-7249 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:	
Unthreaded hole	
Center To Center Distance Between Terminal Rows:	
0.100 inches	
Cubic Measure:	
0.124 cubic inches	
Electrical Resistance Per Section:	
5.0 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
9000.0	
Center To Center Distance Between Center Terminal And Outside Te	rminal:
Between 0.295 inches and 0.305 inches	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Ra	ted Power:
175.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg O	Celsius:
-100.0 to 100.0 single section	
Power Dissipation Rating Per Section In Watts:	
1.0 free air single section	
Resistance Tolerance Per Section In Percent:	
-10.0 to 10.0 single section	
Actuator Travel Control Feature:	
Clutch	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Powe	er:
85.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 pin	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	