NSN 5905-00-017-1417

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-017-1417

Electrical Resistance: 20.000 (Alohoms Resistance Tolerance In Percent: 20.000 (Alohoms Resistance Tolerance In Percent: 20.000 (Ambient Tempurature In Deg Celsius At Full Rated Power: 20.00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 20.00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 20.00 Empurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 to 15.0.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 300y Diameter: 20.318 inches 300y Length: 20.888 inches 300y Length: 20.888 inches 300y Fee air Ziticality Code Justification: Fees Sylve Designator: Avail terminal each end Fees Data Document: 30001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 30101-1820986 drawing this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 30101-1820986 drawing this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 30101-1820986 drawing this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 30101-1820986 drawing this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 30101-1820986 drawing this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 30101-1820986 drawing this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 30101-1820986 drawing this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 30101-1820986 drawing this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 2,000 to 2,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 2,000 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 2,000 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 2,000 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 2,50,10 150,0 Inclosure Method: 2,50,10 150,0 Inclosure Method: 2,50,10 150,0 Inclosure Method: 2,50,10 150,0 Inclosure Method: 3,50,10 150,0 Inclosure Method:	-200.0/+200.0
Resistance Tolerance in Percent: 2.000 to 2.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 85.0 to Tempurature Range Of Tempurature Coefficient in Deg Celsius: 85.0 to 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 85.0 to 150.0 Tempurature Method: 85.0 to 150.0 Tempurature Met	Electrical Resistance:
2.000 to 2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempur	20.000 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 85.0 Empurature Range Of Tempurature Coefficient in Deg Celsius: 85.0 to 150.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Regliability Indicator: Vot established Body Diameter: 9.381 inches Body Length: 9.088 inches Power Dissipation Rating In Watts: 2.000 free air Criticality Code Justification: Fest Style Designator: Vot all terminal each end Fest Data Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; vot culdes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Vot Ditt Of Measure: - Demilitarization: No	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Inclosure Method: Encapsulated Feminal Type: Wire lead Reliability Indicator: Not established 3ody Diameter: 1.318 inches 3ody Longth: 2.088 inches Power Dissipation Rating In Watts: 2.000 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; Excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Juit of Measure: - Demilitarization: No	-2.000 to 2.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 150.0 Tempurature Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 1.0.18 inches Power Dissipation Rating In Watts: 2.000 free air Criticality Code Justification: Fest Style Designator: Exist Bata Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: Excellated Survey Company of Measure: 1.0.10 feet Life: 1.0.10 feet Life: 1.0.10 fees and the document that may be referenced in a basic governing drawing) 1.0.10 feet Life: 1.0.11 for Measure: 1.0.11 feet Measure: 1.0.11 feet Measure: 1.0.12 feet Life: 1.0.13 feet Life: 1.0.14 feet Life: 1.0.15 feet Li	Ambient Tempurature In Deg Celsius At Full Rated Power:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 150.0 nclosure Method: Encapsulated Ferminal Type: Write lead Reliability Indicator: Not established Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Juit Of Measure:	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 150.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Juit Of Measure: - Demilitarization: No	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: incapsulated ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.318 inches Body Dength: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Criticality Code Justification: Fest Style Designator: Avail terminal each end Fest Data Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Juit Of Measure:	150.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating in Watts: 0.000 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc., excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Joint Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 0.000 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: M/a Unit Of Measure: - Demilitarization: No	-55.0 to 150.0
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: Criticality Code Justification: Fest Style Designator: Askala terminal each end Fest Data Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure: - Demilitarization: No	Inclosure Method:
Wire lead Reliability Indicator: Not established Reliability Code Justification: Rest Reliability Indicator Rest Data Document: Rest Reliability Indicator: Reliabil	Encapsulated
Reliability Indicator: Not established Body Diameter: Dial 8 inches Body Length: Diameter: Dial 8 inches Power Dissipation Rating In Watts: Diameter: Dia	Terminal Type:
Not established 30dy Diameter:	Wire lead
Body Length: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Unit Of Measure: Demilitarization:	Reliability Indicator:
2.318 inches 33ody Length: 2.688 inches 2.69wer Dissipation Rating In Watts: 2.6000 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 1.0001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2.001-1820986 drawing (this is the basic governing drawing) Shelf Life: Axial drawing (this is the basic governing drawing) Shelf Life: Axial drawing (this is the basic governing drawing) Shelf Life: Axial drawing (this is the basic governing drawing) Shelf Life: Axial drawing (this is the basic governing drawing) Shelf Life: Axial drawing (this is the basic governing drawing) Shelf Life: Axial drawing (this is the basic governing drawing) Shelf Life: Axial drawing (this is the basic governing drawing) Shelf Life: Axial drawing (this is the basic governing drawing) Shelf Life: Axial drawing (this is the basic governing drawing) Shelf Life: Axial drawing (this is the basic governing drawing) Shelf Life: Axial drawing (this is the basic governing drawing) Shelf Life: Axial drawing (this is the basic governing drawing) Shelf Life: Axial drawing (this is the basic governing drawing) Shelf Life: Axial drawing (this is the basic governing drawing) Shelf Life: Axial drawing (this is the basic governing drawing) Shelf Life: Axial drawing (this is the basic governing drawing)	Not established
Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 1.0001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2.excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Juit Of Measure: Demilitarization:	Body Diameter:
Power Dissipation Rating In Watts: 2.000 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	0.318 inches
Power Dissipation Rating In Watts: 2.000 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: - Demilitarization: No	Body Length:
Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: Demilitarization:	0.688 inches
Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc., excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Power Dissipation Rating In Watts:
Style Designator: Axial terminal each end Fest Data Document: I 0001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: - Demilitarization: No	2.000 free air
Axial terminal each end Test Data Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Criticality Code Justification:
Axial terminal each end Fest Data Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Demilitarization: No	Test
Test Data Document: 10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	Style Designator:
10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: Demilitarization: No	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: Demilitarization:	Test Data Document:
Shelf Life: N/a Unit Of Measure: - Demilitarization:	10001-1820986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Jnit Of Measure: - Demilitarization:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Jnit Of Measure: - Demilitarization: No	Shelf Life:
- Demilitarization:	N/a
No	Unit Of Measure:
No	
	Demilitarization:
	No
·lig:	Fiig:
N001a0	A001a0