NSN 5905-00-018-0948

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-018-0948 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.282 inches **Mounting Bushing Length:** 0.438 inches **Body Length:** 0.563 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 325.0 **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over more than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Hermetically sealed **Electrical Resistance Per Section:** 10.0 kilohms single section **Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:** 180.0 single section **Rotary Actuator Travel In Angular Deg:**

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

135.0 single section

NSN 5905-00-018-0948

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Tap Location Tolerance Per Section:

-1.0 to 1.0 degrees angular rotation single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0