Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-018-0992

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

#### **Overall Length:**

0.812 inches

#### Body Diameter:

0.637 inches

Shaft Diameter:

0.156 inches

Shaft Length:

0.437 inches

#### Mounting Bushing Length:

### 0.438 inches

**Body Length:** 

0.375 inches

#### Overall Diameter:

0.844 inches

### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Nonturn Device Location:

At 9 oclock

#### **Nonturn Device Radius:**

0.375 inches

#### Screw Thread Diameter:

0.250 inches

### Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

200.0 ohms single section

# Power Dissipation Rating Per Section In Watts:

0.3 free air single section



Resistance Tolerance Per Section In Percent:

-30.0 to 30.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0