## NSN 5905-00-019-2387

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-019-2387

Section Quantity:
1
Body Style:
Cylindrical tab/flange mounted
Reliability Indicator:
Not established
Body Diameter:
0.375 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.192 inches
Body Length:
0.480 inches
Shaft Style:
Round, slotted, undercut
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Lateral Distance Between Mounting Hole Centers:
0.562 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Flange
Electrical Resistance Per Section:
2.5 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
100.0 single section
Power Dissipation Rating Per Section In Watts:
0.125 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:

A single section

## NSN 5905-00-019-2387

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



<b>Terminal Type And Quantity:</b>
3 wire loop
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0