NSN 5905-00-020-3238

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-020-3238 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: 0.0600 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0600 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.620 inches **Body Length:** 0.995 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0600 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:** 0.25 inch-ounces **Maximum Running Torque:** 0.25 inch-ounces **Shaft End Play:** 0.00500 inches

Shaft Runout: 0.001 inches

NSN 5905-00-020-3238

Precision Nonwire Wound Variable Resistor - Page 2 of 3



| Lateral Runout: |
|---|
| 0.001 inches |
| Pilot Diameter Runout: |
| 0.005 inches |
| Shaft Radial Play: |
| 0.001 inches |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |
| Clamp ring |
| Electrical Resistance Per Section: |
| 2.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 360.0 |
| Function Conformity Tolerance Per Section: |
| -0.035/+0.035 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 170.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -400.0/+400.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.25 free air single section |
| Function Conformity Per Section: |
| Single section independent linearity |
| Fixed Tap Quantity Per Section: |
| 1 single section |
| Tap Location Tolerance Per Section: |
| -1.0/+1.0 ohms single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0 to 10.0 single section |
| Actuator Travel Control Feature: |
| Continuous motion |
| Tap Location From Ccw Terminal Per Section In Ohms: |
| 1000.0 single section |
| Function Characteristic Per Section: |
| Single section linear |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 125.0 single section |
| Terminal Type And Quantity: |
| 4 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

-

NSN 5905-00-020-3238

Precision Nonwire Wound Variable Resistor - Page 3 of 3



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A002a0