NSN 5905-00-020-3238

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-020-3238 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: 0.0600 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0600 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.620 inches **Body Length:** 0.995 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0600 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:** 0.25 inch-ounces **Maximum Running Torque:** 0.25 inch-ounces **Shaft End Play:** 0.00500 inches

Shaft Runout: 0.001 inches

NSN 5905-00-020-3238

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.005 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
2.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.035/+0.035 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
170.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-400.0/+400.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 ohms single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
1000.0 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
125.0 single section
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5905-00-020-3238

Precision Nonwire Wound Variable Resistor - Page 3 of 3



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A002a0