

View Online at <https://aerobasegroup.com/nsn/5905-00-020-6821>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7500 inches

Pilot Length:

0.0400 inches

Undercut Diameter:

0.750 inches

Undercut Width:

0.0600 inches

Body Diameter:

0.750 inches

Shaft Diameter:

0.125 inches

Shaft Length:

2.241 inches

Body Length:

0.875 inches

Mounting Lip Diameter:

0.7500 inches

Mounting Lip Depth:

0.0400 inches

Undercut Diameter:

0.124 inches

Shaft Style:

Round, stepped

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Undercut Length:

1.500 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.5 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Continuous motion

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0