## NSN 5905-00-021-6259

Composition Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-021-6259

Resistance Tolerance In Percent: -5.000 to 5.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0  Inclosure Method: Encapsulated Terminal Type: Wire lead  Body Diameter: 0.090 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a Unit Of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: Bai349-mill-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	1.100 megohms
Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  130.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Body Diameter:  0.090 inches  Body Length:  0.250 inches  Power Dissipation Rating In Watts:  0.250 inches  Style Designator:  Axial terminal each end  Test Data Document:  81349-mill-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  130.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	-5.000 to 5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  130.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	70.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Encapsulated Terminal Type: Wire lead Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	130.0
Terminal Type:  Wire lead  Body Diameter: 0.090 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.250 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Inclosure Method:
Wire lead  Body Diameter:  0.090 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.250 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Encapsulated
Body Diameter:  0.090 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.250 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Terminal Type:
Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Axial terminal each end  Test Data Document: 81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure: Demilitarization:	Wire lead
Body Length:  0.250 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Body Diameter:
O.250 inches  Power Dissipation Rating In Watts: O.250 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	0.090 inches
Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Body Length:
O.250 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	0.250 inches
Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	0.250 free air
Test Data Document:  81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Style Designator:
81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	81349-mil-r-39008 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a Unit Of Measure:  Demilitarization:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure:  Demilitarization:	Shelf Life:
 Demilitarization:	N/a
	Unit Of Measure:
	Demilitarization:
No	No
Fiig:	Fiig:
A001a0	A001a0