NSN 5905-00-021-6538

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-021-6538

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Terminal Length:
0.594 inches
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.156 inches
Shaft Length:
0.125 inches
Body Length:
1.250 inches
Body Width:
0.250 inches
Body Height:
0.359 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Center To Center Distance Between Terminals:
0.700 inches
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal and unthreaded hole
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:

9000.0

NSN 5905-00-021-6538

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Center	To Center	Distance	Retween	Center	Terminal	And O	utside	Terminal:
Jenier	10 Center	Distance	Detween	Center	i ei iiiiiiai	Allu U	uisiue	i ei iiiiiiai.

0.400 inches

Resistance Tempurature Characteristic Range Per Section In Percent:

+0.0 to 5.5 -55 degrees celsius single section and +0.0 to 3.0 -25 degrees celsius single section and -2.0 to 2.0 85 degrees celsius single section and +0.0 to 4.5 120 degrees celsius single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A002a0