

View Online at <https://aerobasegroup.com/nsn/5905-00-022-3497>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.7490 inches and 0.7500 inches

Pilot Length:

Between 0.0570 inches and 0.0670 inches

Undercut Diameter:

0.781 inches

Undercut Width:

Between 0.0570 inches and 0.0670 inches

Body Diameter:

Between 0.870 inches and 0.880 inches

Shaft Diameter:

0.124 inches

Shaft Length:

Between 0.723 inches and 0.745 inches

Body Length:

4.750 inches

Mounting Lip Diameter:

Between 0.8700 inches and 0.8800 inches

Mounting Lip Depth:

Between 0.0570 inches and 0.0670 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Mounting Facility Quantity:

1

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Unthreaded bushing

Electrical Resistance Per Section:

20.0 percent, rated amperes c and better industrial clears

Power Dissipation Rating Per Section In Watts:

1.5 free air 2nd section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 2nd section

Special Features:

Survo mount with two sections variable resistors and one section switch only

Terminal Type And Quantity:

14 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0