

View Online at <https://aerobasegroup.com/nsn/5905-00-022-3497>

**Section Quantity:**

2

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 0.7490 inches and 0.7500 inches

**Pilot Length:**

Between 0.0570 inches and 0.0670 inches

**Undercut Diameter:**

0.781 inches

**Undercut Width:**

Between 0.0570 inches and 0.0670 inches

**Body Diameter:**

Between 0.870 inches and 0.880 inches

**Shaft Diameter:**

0.124 inches

**Shaft Length:**

Between 0.723 inches and 0.745 inches

**Body Length:**

4.750 inches

**Mounting Lip Diameter:**

Between 0.8700 inches and 0.8800 inches

**Mounting Lip Depth:**

Between 0.0570 inches and 0.0670 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Mounting Facility Quantity:**

1

**Terminal Location:**

Radially positioned over more than half the circumference

**Mounting Method:**

Unthreaded bushing

**Electrical Resistance Per Section:**

20.0 percent, rated amperes c and better industrial clears

**Power Dissipation Rating Per Section In Watts:**

1.5 free air 2nd section

**Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 2nd section

**Special Features:**

Survo mount with two sections variable resistors and one section switch only

**Terminal Type And Quantity:**

14 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0