## NSN 5905-00-023-2036

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-023-2036 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.7495 inches and 0.7505 inches Pilot Length: Between 0.0570 inches and 0.0670 inches **Undercut Diameter:** Between 0.745 inches and 0.755 inches **Undercut Width:** Between 0.0570 inches and 0.0670 inches **Body Diameter:** Between 0.870 inches and 0.880 inches **Shaft Diameter:** Between 0.1246 inches and 0.125 inches Shaft Length: Between 0.657 inches and 0.719 inches **Body Length:** 2.203 inches **Mounting Lip Diameter:** Between 0.8700 inches and 0.8800 inches **Mounting Lip Depth:** Between 0.0570 inches and 0.0670 inches **Shaft Style:** Round **Actuator Type:** Double ended shaft **Shaft End Play:** 0.005 inches **Shaft Radial Play:** 0.0007 inches **Fragility Factor:** Moderately rugged **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** 

Clamp ring

Terminal Type And Quantity:

12 turret

## NSN 5905-00-023-2036

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0