NSN 5905-00-023-2395

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-023-2395

Section Quantity:
1
Body Style:
Cylindrical hole/slot mounted
Reliability Indicator:
Not established
First Flat Length:
1.562 inches
Flat Height:
0.344 inches
Body Diameter:
8.000 inches
Shaft Diameter:
0.375 inches
Shaft Length:
2.000 inches
Body Length:
2.125 inches
Mounting Hole/stud Circle Diameter:
3.000 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
325.0
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
20.0
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:

325.0

NSN 5905-00-023-2395

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts: 500.0 free air single section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Actuator Travel Control Feature: Stops Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization: No

Fiig: A002a0