NSN 5905-00-023-6175

Non-wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-023-6175 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Body Diameter:** 1.093 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.562 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Test Data Document:** 81349-mil94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:**

--

N/a

3 tab, solder lug

Shelf Life:

Unit Of Measure:

NSN 5905-00-023-6175

Non-wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0