NSN 5905-00-023-8206

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-023-8206

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Body Diameter:
1.593 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.500 inches
Body Length:
0.625 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
Trontain Borroo Radiaor
0.531 inches
0.531 inches
0.531 inches Screw Thread Diameter:
0.531 inches Screw Thread Diameter: 0.375 inches
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator:
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi):
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location:
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method:
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Locking bushing
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Locking bushing Electrical Resistance Per Section:
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Locking bushing Electrical Resistance Per Section: 100.000 kilohms single section
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Locking bushing Electrical Resistance Per Section: 100.000 kilohms single section Power Dissipation Rating Per Section In Watts:
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Locking bushing Electrical Resistance Per Section: 100.000 kilohms single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Locking bushing Electrical Resistance Per Section: 100.000 kilohms single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Resistance Tolerance Per Section In Percent:

3 tab, solder lug

Terminal Type And Quantity:

NSN 5905-00-023-8206

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0