

View Online at <https://aerobasegroup.com/nsn/5905-00-025-5933>

Section Quantity:

3

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.062 inches

Shaft Diameter:

Between 0.2495 inches and 0.2500 inches

Shaft Length:

1.000 inches

Mounting Bushing Length:

0.380 inches

Body Length:

2.000 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

350.0

Maximum Starting Torque:

8.00 inch-ounces

Maximum Running Torque:

8.00 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Screw Thread Diameter:

0.469 inches

Screw Thread Series Designator:

Uns

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

100.0 ohms c and better industrial clears

Rotary Actuator Travel In Angular Deg:

350.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 3rd section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-900.0/+900.0 all sections

Power Dissipation Rating Per Section In Watts:

1.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 all sections

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 all sections

Test Data Document:

80249-730645 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

9 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0