NSN 5905-00-026-9151

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-026-9151

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.737 inches
Terminal Length:
0.795 inches
First Flat Length:
0.594 inches
Flat Height:
0.216 inches
Body Diameter:
2.410 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.250 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.440 inches
Overall Diameter:
3.205 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Maximum Starting Torque:
40.00 inch-ounces
Maximum Running Torque:
4.00 inch-ounces
Maximum Stop Torque:
20.00 inch-ounces
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
0.500 inches
Screw Thread Diameter:
0.375 inches
5.57 5 1151150

NSN 5905-00-026-9151 Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Jnef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
_ocking bushing
Electrical Resistance Per Section:
4.0 ohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
50.0 heat sink single section
Resistance Tolerance Per Section In Percent:
10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
31349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
31349-mil-r-22/5 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0