## NSN 5905-00-027-0347

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-027-0347

Electrical Resistance: 34.800 ohms Resistance Tolerance In Percent: 4.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 455.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.1487 inches Body Length: 0.580 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil+-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent:  1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0 to 275.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Dlameter:  0.187 inches  Body Length:  0.560 inches  Power Dissipation Rating In Watts:  3.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Shelf Life:  N/a  Unit Of Measure:	-30.0 to 30.0
Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 225.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 2275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.1687 inches Body Length: 0.560 inches Power Dissipation Rating in Watts: 0.560 inches Power Dissipation Rating in Watts: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	34.800 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0  Inclosure Method: Encapsulated Terminal Type: Wire lead  Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.050 inches Power Dissipation Rating In Watts: 3.000 free air  Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Shelf Life: N/a  Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.050 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a  Unit Of Measure:	-1.000 to 1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0 to 275.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.187 inches  Body Length:  0.560 inches  Power Dissipation Rating In Watts:  3.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  8xi4e Posignator:  8xi3e percentage of the publications, reflecting general type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: Bai349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0 to 275.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.187 inches  Body Length:  0.560 inches  Power Dissipation Rating In Watts:  3.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mill-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", **, etc.).  Shelf Life:  N/a  Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3,000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	275.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	-55.0 to 275.0
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	Encapsulated
Reliability Indicator:  Not established  Body Diameter: 0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator: Axial terminal each end  Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:	Terminal Type:
Note established  Body Diameter:  0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	Wire lead
Body Diameter:  0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	Reliability Indicator:
0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator: Axial terminal each end  Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:	Not established
Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	Body Diameter:
0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	0.187 inches
Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	Body Length:
Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	0.560 inches
Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	3.000 free air
Test Data Document:  81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	Style Designator:
81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	81349-mil-r-26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life:  N/a  Unit Of Measure:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Unit Of Measure: 	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure:	Shelf Life:
- <del>-</del>	N/a
 Demilitarization:	Unit Of Measure:
Demilitarization:	
	Demilitarization:
No	No
Fiig:	Fiig:
A001a0	A001a0