## NSN 5905-00-027-0395

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-027-0395 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 0.410 inches **Terminal Length:** 6.000 inches **Overall Height:** 0.375 inches **Overall Width:** 0.150 inches **Mounting Slot Width:** 0.072 inches **Shaft Diameter:** 0.070 inches **Shaft Length:** 0.035 inches **Body Length:** 0.375 inches **Body Width:** 0.150 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Lateral Distance Between Mounting Hole Centers:** 0.419 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Slot **Electrical Resistance Per Section:** 50.0 kilohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

## NSN 5905-00-027-0395

Demilitarization:

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Power Dissipation Rating Per Section In Watts:                      |
|---|
| 0.75 free air single section  |
| Resistance Tolerance Per Section In Percent:                        |
| -10.0 to 10.0 single section  |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 85.0 single section   |
| Standard Taper Curve Per Section:                                   |
| A single section  |
| Terminal Type And Quantity:   |
| 3 wire lead   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |