## NSN 5905-00-027-0453

**Section Quantity:** 

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-027-0453

1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.156 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.375 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.625 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
340.0
Maximum Starting Torque:
1.00 inch-ounces
Maximum Running Torque:
1.00 inch-ounces
Screw Thread Diameter:
0.375 inches
0.375 inches  Screw Thread Series Designator:
Screw Thread Series Designator:
Screw Thread Series Designator: Unef
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi):
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location:
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method:
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Features Provided:
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Features Provided: Nonmetallic shaft

340.0

## NSN 5905-00-027-0453

Precision Wire Wound Variable Resistor - Page 2 of 2



## **Function Conformity Tolerance Per Section:**

-1.00 to 1.00 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air single section

**Function Conformity Per Section:** 

Single section independent linearity

**Resistance Tolerance Per Section In Percent:** 

-2.0 to 2.0 single section

**Actuator Travel Control Feature:** 

Stops

**Function Characteristic Per Section:** 

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

**Terminal Type And Quantity:** 

3 solder stud

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A002a0