NSN 5905-00-027-5702

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-027-5702
Section Quantity:
3
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.312 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.763 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.705 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Switch Type:
Rotary
Switch Voltage Rating In Volts:
28.0
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
352.0
Maximum Starting Torque:
0.60 inch-ounces
Maximum Running Torque:
0.30 inch-ounces
Shaft End Play:
0.005 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.005 inches
Pilot Diameter Runout:
0.002 inches

0.004 inches

Shaft Radial Play:

NSN 5905-00-027-5702

Precision Wire Wound Variable Resistor - Page 2 of 3



Switch Operating Position: Start of rotation **Switch Contact Arrangement:** Single pole, single throw, normally open, both positions maintained **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Standard bushing **Features Provided:** Switch **Electrical Resistance Per Section:** 5.0 percent, rated amperes c and better select **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -0.50/+0.50 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 all sections **Power Dissipation Rating Per Section In Watts:** 1.0 free air all sections **Function Conformity Per Section:** All sections independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 2nd section **Actuator Travel Control Feature:** Continuous motion **Function Characteristic Per Section:** All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections **Switch Current Type And Rating In Amps:** 0.000040 ac/dc **Terminal Type And Quantity:** 11 turret Shelf Life:

N/a

NSN 5905-00-027-5702

Precision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0