Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-027-8101

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

2.875 inches

#### Terminal Length:

0.156 inches

#### First Flat Length:

0.344 inches

#### Flat Height:

0.219 inches

#### **Body Diameter:**

4.000 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.875 inches

## Mounting Bushing Length:

0.375 inches

#### **Body Length:**

2.000 inches

#### **Overall Diameter:**

4.156 inches

## Shaft Style:

Round, flatted

#### Actuator Type:

Single shaft

## Nonturn Device Location:

At 6 oclock

#### Nonturn Device Radius:

1.875 inches

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# NSN 5905-00-027-8101 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



**Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 100.0 ohms single section **Power Dissipation Rating Per Section In Watts:** 150.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0