NSN 5905-00-033-3573

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-033-3573

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Terminal Length:
0.300 inches
Body Diameter:
Between 0.490 inches and 0.510 inches
Body Length:
Between 0.225 inches and 0.245 inches
Actuator Type:
Recessed drive with slot
Effective Electrical Rotation In Deg Angular Rotation:
315.0
Maximum Starting Torque:
7.50 inch-ounces
Maximum Running Torque:
7.50 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Rear end
Rotary Actuator Travel In Angular Deg:
320.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:

A single section

NSN 5905-00-033-3573

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0