## NSN 5905-00-033-7686

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-033-7686 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.31250 inches Pilot Length: 0.06200 inches **Undercut Diameter:** 1.3125 inches **Undercut Width:** 0.07300 inches **Body Diameter:** 1.422 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.625 inches **Body Length:** 2.666 inches **Mounting Lip Diameter:** 1.43700 inches **Mounting Lip Depth:** 0.09300 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Double ended shaft **Effective Electrical Rotation In Deg Angular Rotation:** 329.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Shaft Runout:** 

0.0015 inches

0.001 inches

**Shaft Radial Play:** 

## NSN 5905-00-033-7686

Precision Wire Wound Variable Resistor - Page 2 of 3



Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Electrical Resistance Per Section:
50.000 percent, rated amperes c and better select
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
66.0 4th section and 132.0 4th section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50 to 0.50 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
62.0 all sections
Power Dissipation Rating Per Section In Watts:
2.0 free air all sections
Function Conformity Per Section:
All sections independent linearity
Fixed Tap Quantity Per Section:
2 4th section
Tap Location Tolerance Per Section:
-2.0/+2.0 degrees angular rotation 4th section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 all sections
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
13 turret
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

No

## NSN 5905-00-033-7686

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0