## NSN 5905-00-034-2122

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-034-2122 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.298 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.406 inches **Overall Diameter:** 1.250 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Maximum Stop Torque:** 128.00 inch-ounces **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.001 inches **Lateral Runout:** 

**Pilot Diameter Runout:** 0.0015 inches

0.003 inches

## NSN 5905-00-034-2122

Precision Wire Wound Variable Resistor - Page 2 of 2



Shaft Radial Play:
0.003 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring and standard bushing
Electrical Resistance Per Section:
50.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-70.0/+70.0 single section
Power Dissipation Rating Per Section In Watts:
2.5 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Decistance Televance Dev Costion In Devecut.
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
-5.0/+5.0 single section
-5.0/+5.0 single section  Actuator Travel Control Feature:
-5.0/+5.0 single section  Actuator Travel Control Feature:  Continuous motion
-5.0/+5.0 single section  Actuator Travel Control Feature:  Continuous motion  Function Characteristic Per Section:
-5.0/+5.0 single section  Actuator Travel Control Feature:  Continuous motion  Function Characteristic Per Section:  7 oclock all primaries
-5.0/+5.0 single section  Actuator Travel Control Feature:  Continuous motion  Function Characteristic Per Section:  7 oclock all primaries  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
-5.0/+5.0 single section  Actuator Travel Control Feature:  Continuous motion  Function Characteristic Per Section:  7 oclock all primaries  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:  60.0 single section
-5.0/+5.0 single section  Actuator Travel Control Feature:  Continuous motion  Function Characteristic Per Section:  7 oclock all primaries  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:  60.0 single section  Terminal Type And Quantity:
-5.0/+5.0 single section  Actuator Travel Control Feature:  Continuous motion  Function Characteristic Per Section: 7 oclock all primaries  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 60.0 single section  Terminal Type And Quantity: 3 turret
-5.0/+5.0 single section  Actuator Travel Control Feature:  Continuous motion  Function Characteristic Per Section: 7 oclock all primaries  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 60.0 single section  Terminal Type And Quantity: 3 turret  Shelf Life:
-5.0/+5.0 single section  Actuator Travel Control Feature:  Continuous motion  Function Characteristic Per Section: 7 oclock all primaries  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 60.0 single section  Terminal Type And Quantity: 3 turret  Shelf Life: N/a
-5.0/+5.0 single section  Actuator Travel Control Feature:  Continuous motion  Function Characteristic Per Section: 7 oclock all primaries  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 60.0 single section  Terminal Type And Quantity: 3 turret  Shelf Life: N/a
-5.0/+5.0 single section  Actuator Travel Control Feature: Continuous motion  Function Characteristic Per Section: 7 oclock all primaries  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 60.0 single section  Terminal Type And Quantity: 3 turret  Shelf Life: N/a  Unit Of Measure:

A002a0