NSN 5905-00-034-3652

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-034-3652

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.291 inches
Body Diameter:
0.355 inches
Body Length:
0.260 inches
Overall Diameter:
0.436 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
320.0
Terminal Location:
Rear end
Mounting Method:
Flange and terminal
Features Provided:
Humidity proof
Electrical Resistance Per Section:
29.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
145.0 single section
Power Dissipation Rating Per Section In Watts:
1.25 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Continuous motion
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section

NSN 5905-00-034-3652

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Precious Material And Location:
Terminals gold and terminals silver
Precious Material:
Gold and silver
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0