

View Online at <https://aerobasegroup.com/nsn/5905-00-036-8698>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

2.500 inches

**Body Diameter:**

1.219 inches

**Shaft Diameter:**

Between 0.188 inches and 0.266 inches

**Shaft Length:**

Between 0.875 inches and 1.250 inches

**Mounting Bushing Length:**

0.500 inches

**Body Length:**

1.250 inches

**Overall Diameter:**

1.425 inches

**Shaft Style:**

Round

**Actuator Type:**

Dual concentric

**Effective Electrical Rotation In Deg Angular Rotation:**

275.0

**Maximum Starting Torque:**

12.00 inch-ounces

**Maximum Running Torque:**

1.00 inch-ounces

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

20.0 ohms 2nd section

**Rotary Actuator Travel In Angular Deg:**

300.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

105.0 all sections

**Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

**Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 1st section

**Actuator Travel Control Feature:**

Stops

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0 to 20.0 1st section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 all sections

**Standard Taper Curve Per Section:**

A all sections

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0