Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-036-8855

# Section Quantity:

1

Body Style:

Cylindrical

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.750 inches

#### **Body Length:**

0.500 inches

#### Shaft Bearing Type:

Bearing

Actuator Type:

Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

270.0

#### Maximum Starting Torque:

10.00 inch-ounces

## Maximum Running Torque:

10.00 inch-ounces

#### **Terminal Location:**

Rear end

#### **Mounting Method:**

Tab

#### **Electrical Resistance Per Section:**

1.0 megohms single section

#### Rotary Actuator Travel In Angular Deg:

270.0

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

#### Power Dissipation Rating Per Section In Watts:

2.0 heat sink single section

#### **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

#### **Actuator Travel Control Feature:**

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

## Standard Taper Curve Per Section:

A single section

### **Terminal Type And Quantity:**

3 tab, solder lug

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0