## NSN 5905-00-038-4051

**Section Quantity:** 

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-038-4051

Reliability Indicator:
Not established
Overall Length:
1.156 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Overall Diameter:
2.093 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
320.0
Maximum Starting Torque:
2.00 inch-ounces
Maximum Running Torque:
0.75 inch-ounces
Screw Thread Diameter:
0.138 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
2
Mounting Method:
Threaded hole
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.35 to 0.35 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section

## NSN 5905-00-038-4051

Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0 to 3.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Special Features:
Mtg holes 0.156 in. Deep spaced 1.800 in. On 0.875 in. Diameter mtg radius
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No