NSN 5905-00-039-7379

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-039-7379 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.440 inches **Terminal Length:** 0.500 inches **Overall Height:** 0.810 inches **Overall Width:**

Mounting Hole Diameter:

0.086 inches

0.250 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.190 inches

Body Length:

1.250 inches

Body Width:

0.250 inches

Body Height:

0.310 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Center To Center Distance Between Terminals:

0.700 inches

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

Terminal Location:

Lower adjacent side single row

Mounting Method:

Unthreaded hole and terminal

Center To Center Distance Between Terminal Rows:

0.100 inches

NSN 5905-00-039-7379

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:

5.0 kilohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

0.300 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0