NSN 5905-00-042-3133

Adjustable Resistor - Page 1 of 1

A001a0



View Online at https://aerobasegroup.com/nsn/5905-00-042-3133

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: 400.0/+400.0 Electrical Resistance: 100.000 ohms Resistance Tolerance In Percent: 5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 nclosure Method: Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic:
Electrical Resistance: 100.000 ohms Resistance Tolerance In Percent: 5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Inclosure Method: Encapsulated Ferminal Type: Fab, solder lug
Resistance Tolerance In Percent: 5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 nclosure Method: Encapsulated Terminal Type: Tab, solder lug
Resistance Tolerance In Percent: 5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/+350.0 Inclosure Method: Encapsulated Ferminal Type: Fab, solder lug
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Inclosure Method: Encapsulated Ferminal Type: Fab, solder lug
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 nclosure Method: Encapsulated Terminal Type: Tab, solder lug
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 nclosure Method: Encapsulated Terminal Type: Tab, solder lug
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 nclosure Method: Encapsulated Ferminal Type: Tab, solder lug
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 nclosure Method: Encapsulated Ferminal Type: Fab, solder lug
55.0/+350.0 nclosure Method: Encapsulated Ferminal Type: Fab, solder lug
nclosure Method: Encapsulated Ferminal Type: Tab, solder lug
Encapsulated Ferminal Type: Fab, solder lug
Ferminal Type: Fab, solder lug
Tab, solder lug
•
Reactance Characteristic:
nductive
Terminal Length:
0.562 inches
Body Diameter:
1.312 inches
Body Length:
5.000 inches
Power Dissipation Rating In Watts:
113.000 free air
Ferminal Width:
0.328 inches
Style Designator:
Radial terminal each end
Test Data Document:
31349-mil-r-19365 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filig: