NSN 5905-00-042-9549

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-042-9549 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.812 inches **Shaft Diameter:** Between 0.2494 inches and 0.2497 inches **Shaft Length:** Between 0.594 inches and 0.656 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** Between 2.719 inches and 2.781 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 5400.0 **Maximum Starting Torque:** 1.30 inch-ounces **Maximum Running Torque:** 0.90 inch-ounces **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.001 inches **Pilot Diameter Runout:** 0.00100 inches **Shaft Radial Play:** 0.001 inches Mechanical Backlash In Deg Angular Rotation: 0.001 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:**

Unef

NSN 5905-00-042-9549 Precision Wire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
15.000 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
900.0 single section
Rotary Actuator Travel In Angular Deg:
5400.0
Function Conformity Tolerance Per Section:
0.50 to 0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
90.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
2 single section
Resistance Tolerance Per Section In Percent:
1.0/+1.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
130.0 to 130.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0