NSN 5905-00-043-0312

Adjustable Resistor - Page 1 of 1

A001a0



View Online at https://aerobasegroup.com/nsn/5905-00-043-0312

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: 400.0/+400.0 Electrical Resistance: 1.500 kilohms Resistance Tolerance In Percent: 5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic: Inductive Terminal Length: 0.359 inches
Electrical Resistance: 1.500 kilohms Resistance Tolerance In Percent: 5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic: Inductive Terminal Length:
Resistance Tolerance In Percent: 5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic: Inductive Terminal Length:
Resistance Tolerance In Percent: 5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 Inclosure Method: Encapsulated Ferminal Type: Fab, solder lug Reactance Characteristic: Inductive Ferminal Length:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic: Inductive Terminal Length:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 to 350.0 Inclosure Method: Encapsulated Ferminal Type: Fab, solder lug Reactance Characteristic: Inductive Ferminal Length:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic: Inductive Terminal Length:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 Inclosure Method: Encapsulated Ferminal Type: Fab, solder lug Reactance Characteristic: Inductive Ferminal Length:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 nclosure Method: Encapsulated Ferminal Type: Tab, solder lug Reactance Characteristic: nductive Ferminal Length:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 nclosure Method: Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic: nductive Terminal Length:
55.0 to 350.0 nclosure Method: Encapsulated Ferminal Type: Fab, solder lug Reactance Characteristic: Inductive Ferminal Length:
nclosure Method: Encapsulated Ferminal Type: Fab, solder lug Reactance Characteristic: Inductive Ferminal Length:
Encapsulated Ferminal Type: Fab, solder lug Reactance Characteristic: Inductive Ferminal Length:
Terminal Type: Tab, solder lug Reactance Characteristic: Inductive Terminal Length:
Γab, solder lug Reactance Characteristic: nductive Ferminal Length:
Reactance Characteristic: nductive Ferminal Length:
nductive Ferminal Length:
Ferminal Length:
0.359 inches
Body Diameter:
0.906 inches
Body Length:
4.000 inches
Power Dissipation Rating In Watts:
55.000 free air
Ferminal Width:
0.328 inches
Style Designator:
Radial terminal each end
Test Data Document:
31349-mil-r-19365 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg: