NSN 5905-00-043-4754

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-043-4754

Section Quantity:
•
Body Style:
Cylindrical servo mounted
Pilot Diameter:
2.87500 inches
Pilot Length:
0.06200 inches
Overall Length:
1.595 inches
Undercut Width:
0.07300 inches
Body Diameter:
3.000 inches
Shaft Diameter:
0.2497 inches
Shaft Length:
0.625 inches
Body Length:
0.625 inches
Overall Diameter:
3.188 inches
Mounting Lip Diameter:
3.00000 inches
Mounting Lip Depth:
0.09300 inches
Shaft Style:
Round
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Maximum Starting Torque:
1.00 inch-ounces
Maximum Running Torque:
0.60 inch-ounces
Shaft End Play:
0.00250 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.005 inches

NSN 5905-00-043-4754 Precision Wire Wound Variable Resistor - Page 2 of 2



Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.004 inches
Mounting Facility Quantity:
1
Terminal Location:
Radially positioned over less than half the circumference
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50 to 0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
7.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A002a0