NSN 5905-00-043-4756

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-043-4756

Electrical Resistance: 33.100 ohms Resistance Tolerance in Percent: 0.020 to 0.020 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Inclosure Method: Incapsulated Ferminal Type: Wire lead Reliability Indicator: Note established 30dy Diameter: 1.250 inches 80dy Length: 1.750 inches Power Dissipation Rating in Watts: 1.250 inches Fower Dissipation Rating in Watts: 1.250 free air Triticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 111293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, ster; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 0.020 to 0.020 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0 to 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0 to 125.0 Tempurature Method: Encapsulated Terminal Type: Within lead Reliability Indicator: Not established Body Diameter: 10.250 inches Body Length: 10.750 inches Power Dissipation Rating In Watts: 10.750 inches Power Dissipation Rating In Watts: 10.750 inches Power Dissipation Rating In Watts: 10.750 inches 10.750 inche	-15.0 to 15.0
Resistance Tolerance In Percent: 0.020 to 0.020 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 125.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 1.750 free air Criticality Code Justification: Test Style Designator: xixial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, stc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wie	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.250 inches Body Length: 1.750 inches Power Dissipation Rating In Watts: 10.250 free air Criticality Code Justification: Test Skyle Designator: Avial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, atc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	93.100 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Availate Terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 125.0 Inclosure Method: Increminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	-0.020 to 0.020
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Retliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, stc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Ambient Tempurature In Deg Celsius At Full Rated Power:
Identification Identification	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 125.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	145.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: I1293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	-55.0 to 125.0
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Fest Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Fest Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Terminal Type:
Note established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Wire lead
Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Reliability Indicator:
Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Not established
Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Body Diameter:
2.750 inches Power Dissipation Rating In Watts: 2.250 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	0.250 inches
Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Body Length:
Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:	0.750 inches
Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:	Power Dissipation Rating In Watts:
Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	0.250 free air
Axial terminal each end Fest Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:	Criticality Code Justification:
Axial terminal each end Fest Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:	Test
Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Style Designator:
11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Axial terminal each end
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Test Data Document:
Shelf Life: N/a	11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
N/a	etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
	Shelf Life:
Jnit Of Measure:	N/a
	Unit Of Measure:
-	
Demilitarization:	Demilitarization:
No	No
Filg:	Fiig:
A001a0	A001a0