NSN 5905-00-044-2223

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-044-2223

180.000 ohms Resistance Tolerance In Percent: -5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 360.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Avial terminal each end Test Data Document: 81349-mil+-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Departure From Cited Designator: Amend millitary 126 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitute the temp coef or res shall not exceed porm 0.0025 pct 1/25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c: paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: Na Unit of Measure: Demilitarization: No Filig: A001s0	Electrical Resistance:
-5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 35.0 Inclosure Method: Encapsulated Terminal Type: Wrie lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitue the temp coef or res shall not exceed porm 0.0025 pct /25 pror/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvotts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure:	180.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mili-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Departure From Cited Designator: Amend military 1-26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitute the temp coef or res shall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c: paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Resistance Tolerance In Percent:
25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Dlameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military 126 paragraph 3.21.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitute the temp coef or resishall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c: paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure:	-5.000 to 5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mili-726 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating in Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military 126 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitute the temp coef or resistal not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	25.0
Inclosure Method: Encapsulated Torminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.21.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitute the temp coef or res shall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Avial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitute the temp coef or resishall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Sheft Life: V/a Unit Of Measure: Demilitarization: No Flig:	350.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating in Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitue the temp coef or resishall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating in Watts: 3,000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitute the temp coef or resishall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Sheft Life: Na Unit Of Measure: Demilitarization: No Fiig:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military 126 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitue the temp coef or resishall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: Na Unit Of Measure: Demilitarization: No Filg:	Terminal Type:
Note established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitute the temp coef or res shall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitue the temp coef or res shall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Reliability Indicator:
0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitue the temp coef or res shall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitue the temp coef or resshall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitue the temp coef or resistall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.188 inches
Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitute the temp coef or resistall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the resistive versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitute the temp coef or resshall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.500 inches
Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitue the temp coef or resshall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitute the temp coef or res shall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3.000 free air
Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitute the temp coef or resshall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitute the temp coef or resishall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the residence versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitute the temp coef or resistall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the resister versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitue the temp coef or resshall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Departure From Cited Designator: Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitue the temp coef or res shall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitue the temp coef or resshall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
shall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Departure From Cited Designator:
degrees c; paragraph 3.15 resistor may be labelled according to commercial practice Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Amend military r 26 paragraph 3.2.1.1 delete 0.00175 and substitute 0.001; amend paragraph 3.5 delete and substitute the temp coef or res
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	shall not exceed porm 0.0025 pct /25 ppm/ per degrees c. Thermal emf of the res wire versus copper shall not exceed 10 microvolts per
N/a Unit Of Measure: Demilitarization: No Fiig:	degrees c; paragraph 3.15 resistor may be labelled according to commercial practice
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0