NSN 5905-00-045-4140

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-045-4140

Body Style: Cylindrical bushing mounted Reliability Indicator: Not established Overall Length: 2.410 inches Body Diameter: 1.680 inches Shaft Diameter: 0.250 inches Shaft Length: 1.000 inches Mounting Bushing Length: 0.375 inches Body Length: 1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section In Watts: 25.0 free air single section	
Body Style: Cylindrical bushing mounted Reliability Indicator: Not established Overall Length: 2.410 inches Body Diameter: 1.680 inches Shaft Diameter: 0.250 inches Shaft Length: 1.000 inches Mounting Bushing Length: 0.375 inches Body Length: 1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Diameter: 0.375 inches Crew Thread Diameter: 0.375 inches Crew Thread Diameter: 0.375 inches Crew Thread Series Designator: Unef Crew Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section In Watts: 25.0 free air single section	Section Quantity:
Cylindrical bushing mounted Reliability Indicator: Not established Overall Length: 2.410 inches Body Diameter: 1.680 inches Shaft Diameter: 0.250 inches Shaft Length: 1.000 inches Mounting Bushing Length: 0.375 inches Body Length: 1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section In Watts: 25.0 free air single section	
Reliability Indicator: Not established Overall Length: 2.410 inches Body Diameter: 1.680 inches Shaft Diameter: 0.250 inches Shaft Length: 1.000 inches Mounting Bushing Length: 0.375 inches Body Length: 1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section In Watts: 25.0 free air single section	
Not established Overall Length: 2.410 inches Body Diameter: 1.680 inches Shaft Diameter: 0.250 inches Shaft Length: 1.000 inches Mounting Bushing Length: 0.375 inches Body Length: 1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section In Watts: 25.0 free air single section	•
Overall Length: 2.410 inches Body Diameter: 1.680 inches Shaft Diameter: 0.250 inches Shaft Length: 1.000 inches Mounting Bushing Length: 0.375 inches Body Length: 1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section In Watts: 25.0 free air single section	
2.410 inches Body Diameter: 1.680 inches Shaft Diameter: 0.250 inches Shaft Length: 1.000 inches Mounting Bushing Length: 0.375 inches Body Length: 1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section In Watts: 25.0 free air single section	
Body Diameter: 1.680 inches Shaft Diameter: 0.250 inches Shaft Length: 1.000 inches Mounting Bushing Length: 0.375 inches Body Length: 1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	
Shaft Diameter: 0.250 inches Shaft Length: 1.000 inches Mounting Bushing Length: 0.375 inches Body Length: 1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	
Shaft Diameter: 0.250 inches Shaft Length: 1.000 inches Mounting Bushing Length: 0.375 inches Body Length: 1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	
Shaft Length: 1.000 inches Mounting Bushing Length: 0.375 inches Body Length: 1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	1.680 inches
Shaft Length: 1.000 inches Mounting Bushing Length: 0.375 inches Body Length: 1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts:	Shaft Diameter:
Mounting Bushing Length: 0.375 inches Body Length: 1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts:	0.250 inches
Mounting Bushing Length: 0.375 inches Body Length: 1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts:	Shaft Length:
Body Length: 1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	1.000 inches
Body Length: 1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Mounting Bushing Length:
1.410 inches Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	0.375 inches
Shaft Style: Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Body Length:
Round Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	1.410 inches
Actuator Type: Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Shaft Style:
Single shaft Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Round
Nonturn Device Location: At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Actuator Type:
At 12 oclock Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Single shaft
Nonturn Device Radius: 0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Nonturn Device Location:
0.500 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	At 12 oclock
Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Nonturn Device Radius:
0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	0.500 inches
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Screw Thread Diameter:
Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	0.375 inches
Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Screw Thread Series Designator:
Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Unef
Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Screw Thready Qty Per Inch (tpi):
Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	32.0
Mounting Method: Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Terminal Location:
Standard bushing Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Radially positioned over less than half the circumference
Electrical Resistance Per Section: 250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Mounting Method:
250.0 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Standard bushing
Power Dissipation Rating Per Section In Watts: 25.0 free air single section	Electrical Resistance Per Section:
Power Dissipation Rating Per Section In Watts: 25.0 free air single section	250.0 ohms single section
25.0 free air single section	-
·	-
Resistance Tolerance Fer Section in Percent:	Resistance Tolerance Per Section In Percent:
Docietanco Toloranco Dor Santian In Darconti	25.0 free air single section

-10.0 to 10.0 single section

NSN 5905-00-045-4140

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0